


Ultra Miniature Toggle & Slide Switches: UT / US Series



Features

- Designed for PCB applications - standard 2.54mm terminal spacing.
- Ultra miniaturised size.
- Bi-furcated contacts for reliable dry circuit working.
- Terminals sealed against ingress of flux.
- Provided with stand-offs for proper cleaning after soldering and maximum mounting stability.
- Case material (PBT) is highly resistant to heat, shock or chemical attack.
- Sealed, long toggle and threaded bush versions available.

Specification


Contact rating	5Vdc 100mA 25Vdc 25mA
Contact current range	0.1µA - 100mA
Initial contact resistance	<20mΩ at 100mV, 1mA
Insulation resistance	1000MΩ at 100Vdc
Dielectric strength	500Vdc for 1 minute
Operating temp. range	-20°C to +80°C
Electrical life	2 pos. >50,000 operations 3 pos. >30,000 operations
Mechanical life	2 pos. >100,000 operations 3 pos. >50,000 operations

Construction

Case	Polybutylene terephthalate (PBT) Glass filled UL94-VO
Frame	Nickel plated steel
Sleeve/Lever	Nickel plated brass
Terminals/Contacts	Phosphor bronze with 1.3µ gold Plate on 3µ nickel barrier.


Slide Switches - US range

US1-1 SPDT straight mount




Part No.			
US1D-1	On	None	On
US1E-1	On	Off	On

US2-1 DPDT straight mount




Part No.			
US2N-1	On	None	On
US2P-1	On	Off	On

US1-2 SPDT angled mount



Part No.			
US1D-2	On	None	On
US1E-2	On	Off	On


US2-2 DPDT angled mount



Part No.			
US2N-2	On	None	On
US2P-2	On	Off	On


Toggle switches - UT range

UT1-1 SPDT straight mount




Part No.			
UT1D-1	On	None	On
UT1E-1	On	Off	On
UT1F-1	On	None	(On)
UT1G-1	(On)	Off	(On)
UT1H-1	On	Off	(On)

UT2-2 DPDT angled mount




Part No.			
UT2N-2	On	None	On
UT2P-2	On	Off	On
UT2R-2	On	None	(On)
UT2S-2	(On)	Off	(On)
UT2T-2	On	Off	(On)

UT2-1 DPDT straight mount



Part No.			
UT2N-1	On	None	On
UT2P-1	On	Off	On
UT2R-1	On	None	(On)
UT2S-1	(On)	Off	(On)
UT2T-1	On	Off	(On)

UT1-2 SPDT angled mount



Part No.			
UT1D-2	On	None	On
UT1E-2	On	Off	On
UT1F-2	On	None	(On)
UT1G-2	(On)	Off	(On)
UT1H-2	On	Off	(On)

Long lever and threaded bush options

Any switch in the UT range may be supplied

- With an 11mm long lever, or
- With a 6mm threaded bush and 9mm lever, or
- With a 6mm threaded bush and 11mm lever.

(Threaded bush versions are fitted with hexagon nuts, lock washers and locating rings)

To order, add appropriate suffix to part number

- Long lever :add suffix (3)
- Threaded bush, 9mm lever :add suffix (5)
- Threaded bush, 11mm lever :add suffix (3)-(5)




Illustration shows UT1D-1-(5)

Sealed versions

Sealed versions of the UT series withstand complete water submersion, Freon or ultrasonic cleaning, steam cleaning and include shaft "O" ring, bushing "O" ring and lead frame "O" ring.

To order add suffix "S" to part number.

Devlin Electronics Limited

Unit D1, Grafton Way, Basingstoke, Hampshire, RG22 6HZ, England.

Telephone: Basingstoke (01256) 467367 Fax: (01256) 840048



DL230218